

XL SERIES



- XL-RAY YABANCI MADDE AYIRICI
- РЕНТГЕНОВСКАЯ МАШИНА ДЛЯ КОНТРОЛЯ
- آلة الفحص بالأشعة السينية
- MACHINE D'INSPECTION À RAYONS XL
- MÁQUINA DE INSPECCIÓN POR RAYOS XL
- MÁQUINA DE INSPEÇÃO POR RAIO XL

■ Widely used in bottled, canned and box-packaged foods delivered uprightly.



Milk powder
Stainless steel detection image.



Canned abalone
glass detection image.



Canned asparagus spear.



Canned asparagus spear
bottom detection image.

Model	XL-12015
Sensitivity (no-load)	SUS ball<Ø0.3mm SUS wire>Ø0.2×2mm
Material size	Diameter<150mm, Height<250mm
Infeed belt width	150mm
Dimensions (L × W × H)	5000 × 1460 × 1980 mm
Net weight (kg)	900
Load (kg)	10
X-Ray output	480W Max 120kv/8.0mA
Infeed belt speed	10-50m/min adjustable.
Interface	17" LCD touch screen.
X-Ray leakage	<1 Sv/h
Protection Level	IP65 for drive parts, IP54 for others.
Power supply	Single phase AC220V±10%, 50/60Hz, 4.5kw.
Service environment	Ambient temperature 0-40°C Relative humidity 30-85% No condensation, no freezing, upheaval.

XM SERIES

- XM-RAY YABANCI MADDE AYIRICI
- РЕНТГЕНОВСКАЯ МАШИНА ДЛЯ КОНТРОЛЯ
- آلة الفحص بالأشعة السينية
- MACHINE D'INSPECTION À RAYONS XM
- MÁQUINA DE INSPECCIÓN POR RAYOS XM
- MÁQUINA DE INSPEÇÃO POR RAIO XM



Push board removal.




Turning removal.

■ Widely used in dairy products, baked food, meat, additives, leisure food, etc.



Yeast powder



Yeast powder (original image)



Yeast powder (marked image)

Model	XM-12060
Sensitivity (no-load)	SUS ball<Ø0.3mm SUS wire>Ø0.2×2mm
Material size	Width<580mm, Height<300mm
Infeed belt width	680mm
Dimensions (L × W × H)	2250 × 1380 × 2110 mm
Net weight (kg)	700
Load (kg)	50
X-Ray output	480W Max 120kv/8.0mA
Infeed belt speed	10-40m/min adjustable.
Interface	17" LCD touch screen.
X-Ray leakage	<1 Sv/h
Protection Level	IP65 for drive parts, IP54 for others.
Power supply	Single phase AC220V±10%, 50/60Hz, 2.5kw.
Service environment	Ambient temperature 0-40°C Relative humidity 30-85% No condensation, no freezing, upheaval.