

- BANT TIPLI ÇOK KULLANIMLI RENK AYIRICI
- МНОГОФУНКЦИОНАЛЬНЫЙ ФОТОСОРТАТОР ЛЕНТОЧНОГО ТИПА
- نوع الحزام متعدد
- TRIEUR DE COULEURS MULTI-USAGE DE TYPE COURROIE
- CLASIFICADOR POR COLOR MULTIUSO TIPO CORREA
- CLASSIFI CODOR DE CORES MULTIUSO TIPO FITA



- DOUBLE LAYER DESIGN EASY FOR SECOND SORTING.
- Stepless Dimming System.
- Extended Front-drive Transmission Structure.
- Transmission System 3.0
- Crash-prevented Separation Design.
- Split ash Cleaning Structure (optional).

#### NUT SORTING SOLUTIONS

##### Hazelnut



Accepts



Discolored Kernel

##### Macadamia nut



Accepts



Rotten nut

##### Almond



Accepts



Discolored Kernel

##### Apricot kernel



Accepts



Peeled kernel

##### Pistachio



Accepts



Discolored Kernel

##### Walnut



Accepts



Discolored kernel

##### Pine nut



Accepts



Discolored Kernel

##### Pecan



Accepts



Rotten pecan

Configuration	Performance	Key Components	15-inch LCD screen	■
			Micron-sized superior HD color sensor	■
Intelligence	Intelligent System	Compound lighting system	-	■
		Crash-prevented maglev ejector	■	■
		New prism spectroscopic imaging technology	-	■
		Targeted positioning	■	■
		Gentle removal	■	■
		Shape sorting	●●●●●	■
		Shell & kernel separation	-	■
		Discolored impurities (plastics, stones, dead insects, glass)	●●●●●	■
		Patented maglev ejector	●●●●●	■
		LED	●●●●●	■
Machine Protection	Air Circuit System	Enhanced point-to-point dust sucking system	■	■
		Input protection cover	-	■
		Remote separation chamber protection	-	■
		Worry-free transmission structure	-	■
		Waterproof and dustproof IP65	-	■
Machine Protection	Intelligent System	Extra-simplified interface	-	■
		Sorter care	-	■
		Remote control	-	■
		Remote commissioning	-	■
		Auto-backup	-	■

Parameters above are tested on the environment of 25°C and 2% impurities rate and may change in different conditions. ● :Function strength, ■ :Standard, □ :Selection - :No

#### Technical Specifications

Model	Channels	Power	Supply voltage	Air pressure	Air consumption	Dimension (L-W-H)	Weight (kg)
BS8	480	4.5	180-240V 50Hz	0.6-0.8 Mpa	<6.0m³/min	3856 × 2100 × 2562	2500